



Crane Rail



		Weight		Head width A		Height H		Base width B		Web S	
		kg/m	lb/yd	mm	in.	mm	in.	mm	in.	mm	in.
American profiles											
ASTM	CR175	86.80	175.00	107.95	4 1/4	152.40	6	152.40	6	38.10	1 1/2
A759/2000	CR171	84.83	171.00	109.22	4.30	152.40	6	152.40	6	31.75	1 1/4
	CR135	66.97	135.00	87.31	3 7/16	146.05	5 3/4	131.76	5 3/16	31.75	1 1/4
	CR105	52.09	105.00	65.09	2 9/16	131.76	5 3/16	131.76	5 3/16	23.81	15/16
	CR104	51.59	104.00	63.50	2 1/2	127.00	5	127.00	5	25.40	1
European Profiles											
DIN	A150	150.30	302.99	150.00	5.91	150.00	5.91	220.00	8.66	80.00	3.15
536/1991	A120	100.00	201.59	120.00	4.72	105.00	4.13	220.00	8.66	72.00	2.83
	A100	74.30	149.78	100.00	3.94	95.00	3.74	200.00	7.87	60.00	2.36
	A75	56.20	113.29	75.00	2.95	85.00	3.35	200.00	7.87	45.00	1.77
	A65	43.10	86.88	65.00	2.56	75.00	2.95	175.00	6.89	38.00	1.50
	A55	31.80	64.11	55.00	2.17	65.00	2.56	150.00	5.91	31.00	1.22
	A45	22.10	44.55	45.00	1.77	55.00	2.17	125.00	4.92	24.00	0.94